

FILLING CAPACITIES

Unit	Specification	Quantity per unit in ccm
Engine	engine oil SAE 15 W/50 - MIL-L-2104 B	7000 ⁽¹⁾ 6500 ⁽²⁾
Gearbox	gear oil SAE 90 - MIL-L-2105	2000
Auxiliary gearbox	gear oil SAE 90 - MIL-L-2105	2600 ⁽¹⁾ 2300 ⁽²⁾
Axle drive	gear oil SAE 90 - MIL-L-2105	2300 ⁽¹⁾ 2000 ⁽²⁾
Wheel drive front	gear oil SAE 90 - MIL-L-2105	400 ⁽³⁾
Wheel drive rear	gear oil SAE 90 - MIL-L-2105	350
Steering	gear oil SAE 90 - MIL-L-2105	650
Hydraulic brake	brake fluid - 4x4 - SAE-J-1703 brake fluid - 6x6 - SAE-J-1703	500 550
Hydraulic clutch	brake fluid - SAE-J-1703	200
Hydraulic gearshift	brake fluid - 4x4 - SAE-J-1703 brake fluid - 6x6 - SAE-J-1703	400 430

(1) New filling

(2) Oil change

(3) In case of new filling fill in 250 cm³ additionally into front axle - joint ball through bore for the upper king pin, or refill to highest level after about 1 km route respectively (see chapter "H" - Wheel Drive, page 10, item 9).